

**LISTING OF THE CLAIMS:**

This Listing of the Claims replaces all previous versions of the claims. Please amend the claims as follows.

1. **(Currently Amended)** A method in an emulation system, comprising:
  - receiving a first sample of state data;
  - selecting a first data of interest from the first sample of state data, wherein the first data of interest is a first subset of bits of the first sample of state data and includes at least first and second portions separated from each other by at least one bit that is not part of the first data of interest;
  - determining if residual storage space in a first buffer exists; ~~and~~
  - storing the first data of interest from the first sample of state data in said first buffer if it is determined that residual storage space in the first buffer exists, such that the first and second portions of the first data of interest as stored are no longer separated from each other by the at least one bit, and otherwise storing said first data of interest in a second buffer such that the first and second portions of the data of interest as stored are no longer separated from each other by the at least one bit;
  - receiving a second sample of state data; and
  - selecting a second data of interest from the second sample of state data, wherein the second data of interest is a second subset of bits of the second sample of state data and wherein bit locations of the first data of interest and the second data of interest are different.
2. **(Currently Amended)** The method of claim 1, further comprising determining whether the first buffer is full after storing the first data of interest from the first sample in the first buffer.
- 3-7. **(Canceled)**

8. **(Currently Amended)** The method of claim 1, further comprising:  
~~receiving a second sample of state data;~~  
~~selecting data of interest from the second sample of state data, wherein the data of interest is a subset of bits of the second sample of state data and includes at least first and second portions separated from each other by at least one bit that is not part of the data of interest; and~~  
storing the second data of interest from the second sample of state data .
9. **(Currently Amended)** The method of claim 8, wherein storing the second data of interest from the second sample of state data comprises:  
determining if residual storage space in the first buffer exists after storing the first data of interest from the first sample of state data; and  
storing at least a portion of the second data of interest from the second sample of state data in the first buffer if residual storage space in the first buffer exists after storing the first data of interest from the first sample of state data.
10. **(Previously Presented)** The method of claim 1, wherein receiving comprises receiving the first sample of state data from a reconfigurable emulation resource.
- 11-15. **(Canceled)**
16. **(Previously Presented)** The method of claim 1, further comprising storing information associated with the first sample of state data.
17. **(Previously Presented)** The method of claim 16, wherein the information comprises a bit position of the data of interest of the first sample of state data.
18. **(Previously Presented)** The method of claim 16, wherein the information comprises an identification of a pin associated with the first sample of state data.

19. **(Currently Amended)** The method of claim 16, further comprising:

~~receiving a second sample of state data;~~

selecting the second data of interest from the second sample of state data, wherein the second data of interest is ~~a subset of bits of the second sample of state data~~ and includes at least third ~~first~~ and fourth ~~second~~ portions separated from each other by at least one bit that is not part of the second data of interest

storing the second data of interest from the second sample of state data;

storing information associated with the first sample of state data in memory; and

storing information associated with the second sample of state data in memory.

20. **(Currently Amended)** An apparatus, comprising:

a first select logic device configured to receive samples of state data, to select data of interest from each of the samples of state data, the data of interest having non-contiguous bits, and to sort the data of interest such that the non-contiguous bits become contiguous, wherein selected bit locations of the data of interest from at least two samples are different;

first and second buffers coupled to the first select logic device and configured to receive the sorted data of interest in an alternating manner by filling the first and second buffers in an alternating manner;

a second select logic device coupled to the first and second buffers and configured to select the first and second buffers in an alternating manner to drain the selected buffer; and

an output storage device coupled to the second select logic device and configured to receive data drained from the selected one of the first and second buffers.

21. **(Original)** The apparatus of claim 20, wherein the first select logic comprises a multiplexer.

22. **(Original)** The apparatus of claim 20, wherein the second select logic device comprises a multiplexer.

23. **(Previously Presented)** The apparatus of claim 20, wherein the first select logic device is configured to send the data of interest to the second buffer responsive to the first buffer becoming full.

24. **(Original)** The apparatus of claim 20, wherein the first select logic device comprises a data of interest sorter.

25. **(Previously Presented)** The apparatus of claim 20, further comprising:  
a memory configured to store information associated with the samples of state data.

26. **(Previously Presented)** The apparatus of claim 25, wherein the information comprises at least a bit position of data of interest of the sample of state data.

27. **(Previously Presented)** The apparatus of claim 25, wherein the information comprises an identification of a pin associated with each of the samples of state data.

28. **(Previously Presented)** The apparatus of claim 20, wherein the output storage device is configured to store information associated with each of the samples of state data.

29. **(Currently Amended)** A method for associating trace data chains with pins of an integrated circuit, the method comprising steps of:

determining a trace data fill rate of each of a plurality of trace data chains; and  
determining a schedule for associating a plurality of pins with the plurality of trace data chains to transfer data out of the trace data chains based at least upon the determined trace data chain fill rates, wherein one of the plurality of pins is shared by at least two trace data chains.

30. **(Currently Amended)** In an emulation debugging resource, a method comprising steps of:

determining fill rates of a plurality of trace data chains;

determining a schedule for associating a plurality of pins with the plurality of trace data chains based at least upon the determined fill rates; and

associating a set of the plurality of trace data chains with the plurality of pins in accordance with the determined schedule, wherein one of the plurality of pins is shared by at least two trace data chains.

31. **(Currently Amended)** In an integrated circuit, the integrated circuit including an emulator, an apparatus comprising:

a plurality of trace data chains;

a trace pin select logic device coupled to the plurality of trace data chains to select a set of the plurality of trace data chains;

a plurality of pins; and

a memory coupled to the trace pin select logic device and configured to store a schedule to associate the selected set with the pins based at least upon determined trace data chain fill rates of the set, wherein one of the plurality of pins is shared by at least two trace data chains.

32. **(Currently Amended)** The method of claim 1, further comprising:

~~receiving a second sample of state data;~~

selecting the second data of interest from the second sample, wherein the second data of interest of the second sample ~~is a subset of bits of the second sample and~~ includes at least third ~~first and fourth second~~ portions separated from each other by at least one bit that is not part of the data of interest of the second sample; and

storing the second data of interest from the second sample in one of said first and said second buffers if residual storage space exists in the one of said first or said second buffer such that the third and fourth ~~first and second~~ portions of the second data of interest as stored are no longer separated from each other by the at least one bit and such that the second data of interest from the second sample is stored so as to be contiguous with the stored first data of interest from the first sample.